



Indoor network minidome fix lens 1,3 MPX

G372-2101

Main features

- 1/3" progressive scan CMOS
- Up to 1.3 megapixel (1280x96) resolution
- HD720P real time video
- H264/MPEG4/MJPEG video compression
- Day: night autoswitch
- Support dual stream, and the sub-stream for mobile surveillance
- PoE (Power over Ethernet)
- 3-axis (pan/tilt/rotation) positioning allows adjustment for optimum camera rotation and position
- Vandal-proof housing



GUNNEBO[®]
For a safer world

Indoor network minidome fix lens 1,3 MPX

G372-2101 1.3 megapixel CMOS Weather-proof Vandal-proof Network Mini dome Camera	
CAMERA	
Image sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.01 Lux @ (F1.2, AGC ON) 0.028 Lux @ (F2.0, AGC ON)
Shutter Speed	1/25s to 1/100,000s
Lens	2.8mm @ F2.0
	Angle of view: 89°
Lens Mount	M12
Angle Adjustment	Pan: ± 15°, Tilt: 0°–90°, Rotation: ± 15°
Day & Night	Electronic
Digital Noise Reduction	DNR
COMPRESSION STANDARD	
Video Compression	H.264/MPEG4/MJPEG
Video Bit Rate	32Kbps–16Mbps
Dual Stream	Yes
IMAGES	
Max. Resolution	1280×960
Frame Rate	50Hz: 25fps (1280×960), 25fps (1280×720) 60Hz: 30fps (1280×960), 30fps (1280×720)
Image Setting	Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
NETWORK	
Network Storage	NAS (iSCSI optional)
Alarm Trigger	Motion detection
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1x, QoS, HTTPS (SIP, SRTP, IPv6 optional)
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, CGI, GENETEC
INTERFACE	
Communication Interface	1 RJ45 10M/100M Ethernet port
Reset Button	Yes
GENERAL	
Operating Conditions	–25°C to 60°C (–13°F to 140°F) Humidity 95% or less (non-condensing)
Power Supply	12V DC ± 10% PoE (802.3af)
Power Consumption	Max. 4W
Impact Protection	IEC60068-275Eh, 50J; EN50102, up to IK10
Ingress Protection level	IP66 (Internal use recommended)
Dimensions	99.9×97.5×46.5mm (3.93" × 3.84" × 1.83")
Weight	250g (0.55lbs)
Gunnebo Reference	APQM53