Strong, stable, low-weight filing cabinets, approved for the protection of documents from fire



The File III 60

FIRE-RESISTANT DOCUMENT PROTECTION

Key Features

- Approved for one hour's fire protection of documents in fire class 60 Paper in accordance with NT Fire 017.
- Two cabinet depths with maximised storage capacity – the 31" cabinet is available with 2, 3 or 4 drawers and the 23" cabinet with 2 or 4 drawers.
- Low-weight cabinets for reduced transportation and installation costs, and lighter floor loads.
- All models are available in A4 format, with Folio format also available for the 31" cabinet.
- Insulation between drawers means each drawer's contents are protected in a fire even if one drawer is left open.
- All models fitted with day-catch locking for extra protection.

- For easier access, high-strength slides allow drawers to be pulled out 110%.
- Interlocking system prevents more than one drawer being open at once and eliminates risk of tipping.
- Entire inner body lined with steel for protection from insulation dust.
- All cabinets fitted with high-quality key lock as standard.
- Light grey, powder-coated finish and smooth-edge design.
- The File III 60 is manufactured in accordance with ISO 9001 for quality management systems and ISO 14001 for environmental management systems.













Chubbsafes
Trusted the world over.

Product Specifications


	External (mm)			Internal (mm)*				
Model	Height	Width	Depth	Height	Width	Depth	Weight (kg)	Capacity (mm)
23" – 2 Drawer (A4)	736	465	572	288	330	461	95	922
23" – 4 Drawer (A4)	1410	465	572	288	330	461	174	1844
31" – 2 Drawer (A4)	736	465	771	288	330	660	126	1320
31" – 3 Drawer (A4)	1073	465	771	288	330	660	165	1980
31" – 4 Drawer (A4)	1410	465	771	288	330	660	216	2640
31" – 2 Drawer (Folio)	736	525	771	288	390	660	129	1320
31" – 3 Drawer (Folio)	1073	525	771	288	390	660	181	1980
31" – 4 Drawer (Folio)	1410	525	771	288	390	660	234	2640

^{*}Internal dimensions per drawer


Lock Options

The File III 60 filing cabinets are fitted with a single high-quality key lock as standard. As an option, a combination lock may also be added for dual central locking. In addition, each individual drawer may be fitted with its own key lock. An electronic lock is available on request. Every model also has day-catch locking so that even when unlocked centrally, a drawer need only be pushed shut to guarantee the full protection of its contents.

Internal Fittings



Data media insert (for 31" model only)



Bottom plate

Fire Testing

The File III 60 has been approved in accordance with the established European standard, NT Fire 017, in fire class 60 Paper, which means the filing cabinet will protect paper documents for one hour. The certification was awarded by SP (Swedish National Testing and Research Institute).

Test Procedure

Stage 1


The cabinet is placed in a furnace and heated to a temperature of almost 1000 °C for 60 minutes to simulate the effects of a severe fire.



Stage 2

The cabinet is removed from the furnace and cooled. When opened, the inner temperature of the cabinet must not exceed 150 °C.





Tilt support for bottom plate



